

Cee-Bee[®] E-3000

Cee-Bee[®] E-3000 is a hydrogen peroxide-activated paint stripper designed for removing polyurethane, epoxy and other paint systems.

Conforms To

- Airbus
- Air Canada
- AMS
- ANA
- Boeing
- Bombardier
- Delta Airlines
- Leonardo Helicopters
- Safran

Full Details on Page 2

Benefits

- Contains no halogenated solvents, phenol or heavy metals.
- Provides excellent removal of polyurethane, epoxy and other paint systems.
- Thixotropic - Clings to vertical, inclined and overhead surfaces.
- Slow drying for maximum reaction time.
- Safe on all aircraft structural metals.
- Environmentally neutral.
- Low odor.
- Low VOC.

Properties

- Viscous Liquid
- Mild Odor

Notes Prior to Handling

Before using your Cee-Bee[®] products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee[®] representative before proceeding.

Conforms To (Continued)

- Airbus
 - CML 09BBA1 – (Unrestricted)
- Air Canada
 - SPEC. 3135-00-007, Rev. D
- AMS
 - AMS 1375
- ANA
 - EI-A-1578, Rev. H
- Boeing
 - AMM 737, 747, 767, 777
 - DPM 5549-5
 - D6-17487, Rev. P
 - BAC 5725
- Bombardier De Havilland
 - DHMS S5.03, Grade 2 (QPL)
- Delta Airlines
 - EA: 10-489048-14
- Embraer
 - MEP 21-016 (QPL)
- Leonardo Helicopters
 - BM310R0001
- Safran
 - DMR 70-129

Use Procedure

Stripping Procedure

1. Optimum performance is attained at temperatures between 75 - 87°F (24 - 30°C).
2. The surface to be stripped should be clean and completely dry.
3. Spray an even, medium coat of Cee-Bee® E-3000 using a high pressure 5:1 (or larger) air activated pump equipped with proper spray tips. Starting from the bottom of the aircraft and working upward.
4. Keep the surface wet with stripper until the paint buckles.
5. When the paint is lifted, agitate the surface to remove the loosened paint.
6. Reapply stripper as required.
7. When all the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual stripper.
8. For best results, apply a mild alkaline cleaning solution (Super Bee™ 210, Super Bee™ 300 LF/G or other cleaner approved for aircraft exteriors) to effectively remove paint and stripper residue.
9. Thoroughly rinse the surface with water.

! Caution

Mixing or cross-contamination of acid-activated strippers with hydrogen peroxide-activated stripper can be highly corrosive to aluminum.

Prior to applying any paint stripper, the following precautions should be taken to prevent any mixing of acid activated strippers with peroxide-activated strippers.

- Thoroughly clean all paint stripping equipment (spray guns, pots, pumps and pressure hoses, etc.) per the equipment manufacturer's recommendations.
- Use a dedicated pump for each stripper type when mixing the container before application and when applying stripper to aircraft.
- If a peroxide-activated stripper is used initially to strip paint, but it's necessary to then use an acid-activated stripper (or vice-versa) to remove residual paint/primer, the aircraft must be thoroughly washed down with water to remove all residue of the initial stripper before applying the other type of stripper. The aircraft should be allowed to dry after washing before applying paint stripper.

! Safety, Handling, and Precautions

- Skin or eye contact can cause irritation. Chemical goggles, face shield, chemical-resistant gloves and protective clothing sufficient to avoid contact are recommended.
- In case of accidental contact, flush area thoroughly with water. If irritation persists, seek medical attention.
- Do not take internally.
- Use in well-ventilated areas.
- Storage area should be cool, dry, well ventilated, and out of direct sunlight. The storage area should have a temperature range of 40° - 77°F (5° - 25°C).
- **Do not store used stripper and removed coatings in closed container as an exothermic (severe heat) reaction may occur.**
- **Spent drums from Cee-Bee[®] E-3000 should be thoroughly rinsed before disposal.**
- **If used stripper is placed back into the original Cee-Bee[®] E-3000 drums, these drums MUST first be rinsed thoroughly and only closed with a vented cap.**

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee[®] E-3000 is a hydrogen peroxide-activated paint stripper designed for removing polyurethane, epoxy and other paint systems.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 11/2024 (Rev. A6)